

Generic: Why do I have to reset the modem and what's this story about MAC addresses ?

A MAC (Media Access Control) Address is a unique identifier. You can have 10 of the same NICs, but each one has its own MAC. They're hard coded into the firmware when they're made.

If you unplugged your router from your Cable modem and plugged a PC directly into it, you might have to reset the modem.

Same holds true if

you had a PC directly connected to your modem and then plugged in your router, you might have to reset the modem. Your ISP sees that MAC address of the device that's connected to the modem and keeps it in a database. If you unplugged one device and plugged in a different one, it now sees a different MAC and doesn't know what to do. When you reset your modem, it releases that MAC address and then waits for another when the modem comes back on.

Kinda like release/renew an IP address, 'cept it's going the other way.

If you look in your router's config screen right now, you might see the MAC address that it is showing to your ISP. If you disconnected your router, plugged a PC into it directly and reset the modem, your ISP would then see a different MAC. You can check that by doing 'ipconfig/all' from a command prompt. You will see something called the 'Physical Address', that's the MAC address of the device and what your ISP sees.

When you have other PC's behind your router/firewall, all your ISP sees is the MAC address of the device connected to your modem, nothing else. The router takes care of that after it goes through it.

Troubleshooting :

- IMPORTANT : That works for cable access.

- Try to connect a computer right on your cablemodem and see if your ISP sees your new MAC address. When so, just put the NIC that you use right now in your freesco box and you don't have to worry about MAC addresses at all. Just make sure you put it in the right pci slot. The one that freesco sees as eth0. You might have to switch your NIC's and cables around to get it going.

- It also helps to write down the IP, DNS and gateway numbers from that NIC. You have to fill them in on eth0.

Generic: Why do I have to reset the modem and what's this story about MAC addresses ?

Unique solution ID: #1150

Author: Mathieu CATTIN

Last update: 2004-12-08 00:35